

The New CXi V-Twin.

Commercial performance. Unmatched durability.



Commercial performance, reliable power.

The CXi Series V-Twin engines are specially designed for zero turn mowers and other high-debris applications to endure extended use in extreme conditions. Our patented 5-Step Debris Management System and cyclonic air filter keep harmful debris out of the engine, extending engine life. The V-Twin design delivers more power, is naturally balanced for less vibration, runs cooler and cleaner. These robust engines are built to get the job done.

NEW Optional Oil Xtend™ System

250-hour oil & filter change

Extended maintenance interval includes oil, oil filter, fuel filter, air filter and spark plug.

Automotive-style oil filter

- 20% more efficient and 45% more dust holding capacity than premium spin-on filter.
- 14% increase in oil capacity.
- 6x larger oil filter housing and EZ Oil Drain Hose make oil changes quick, clean and easy.
- Finned aluminum housing acts as an oil cooler. Available for 23.0, 25.0, 27.0 Gross HP.*

NEW Optional High Inertia Flywheel

- Reduced engine vibration.
- Smoother power delivery.
- Improved shock load acceptance.

NEW High Torque Cam[‡]

More usable power for the toughest conditions.

NEW Optional EFI/ETC

- Electronic Fuel Injection (EFI) system provides improved starting, smooth performance, quick load acceptance and reduced fuel consumption.
- Electronic Throttle Control (ETC) technology allows for consistent power and quality of cut no matter the terrain or load.

Available for 25.0 and 27.0 Gross HP.*

Commercial-Grade Engine Block and Sump

Commercial engine base structure and gaskets provide strength and durability.

Best-In-Class Debris Management (Standard)

5-Step Cyclonic Debris Management System keeps harmful debris out of the engine for durability under heavy-debris conditions.

All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

Clean-out panels enable quick debris inspection and cleaning.



US MARKETS

EMEA MARKETS

| MODEL | CXi2000 | CXi2300 | CXi2500 | CXi2700 | 7220CXi | 8290CXi |
|-------|-------------------|-------------------|-------------------|-------------------|---------------------------------------|---------------------------------------|
| POWER | 20.0 GROSS HP* | 23.0 GROSS HP* | 25.0 GROSS HP* | 27.0 GROSS HP* | 39,57 NM GROSS TORQUE [†] | 47,48 NM GROSS TORQUE [†] |
| СС | 656 | 724 | 724 | 810 | 656 | 724 |

BRIGGS & STRATTON

Milwaukee, WI 53201-0702 USA (414) 259-5333

EMEA OFFICE

Wolleraustrasse 41 8807 Freienbach, Switzerland +41 (0)55 415 1200 Copyright ©2024. All rights reserved.



All power levels are stated gross torque at 2600 RPM per SAE J1940 as rated by Briggs & Stratton.
"See briggsandstratton.com for complete warranty details. ‡ EFI models only.